

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Cancelled)
2. (Withdrawn): A display apparatus of claim ~~1~~ 42, wherein  
said storing circuit comprises a predetermined number of storing elements, said number corresponding to the number of bits in said digital image signal; and  
said signal selector selects a signal to be supplied to said display element from among a predetermined number of signals, said number corresponding to the number of bits in said digital image signal.
3. (Withdrawn): A display apparatus of claim ~~1~~ 42, wherein,  
said storing circuit stores said digital image signal using one or more inverters.
4. (Cancelled).
5. (Withdrawn): A display apparatus of claim ~~1~~ 42, wherein,  
said plurality of display pixels is capable of displaying a still image.
6. (Withdrawn): A display apparatus of claim ~~1~~ 42, wherein,  
after a still image is written to each of said plurality of display pixels as a digital image signal, operations of driving circuits for driving said plurality of display pixels are stopped until a new digital image signal is written to the same display pixels.

7. (Withdrawn): A display apparatus of claim ~~1~~ 42, wherein,  
said display apparatus is a liquid crystal display apparatus; and  
said display element includes a liquid crystal capacitor and a pair of  
electrodes for driving said liquid crystal capacitor.

8. (Withdrawn): A display apparatus of claim 7, wherein,  
said pair of electrodes for driving said liquid crystal capacitor  
comprises an individual display electrode for each display pixel and a facing  
electrode provided to face said display electrode; and

at least one of the signals selected by said signal selector is an  
alternating current voltage signal which oscillates around the voltage of said facing  
electrode.

9. (Cancelled):

10. (Currently Amended): A display apparatus, comprising:  
a plurality of gate lines provided in one direction of a substrate;  
a plurality of drain lines provided in a direction intersecting with said  
gate lines; and

a plurality of display pixels, each of which is selected by a scan signal  
supplied from corresponding one of said plurality of gate lines, and which is  
supplied with an image signal from corresponding one of said plurality of drain  
lines; wherein

each of said plurality of display pixels comprises:

a display element;

a first display circuit having a storing circuit, for storing a digital  
image signal from said corresponding one of drain lines in response to a scan signal

from said corresponding one of gate lines, and a signal selector which is operated based on data stored at said storing circuit for selecting an output signal from among two or more display signals and supplying said selected signal to said display element; and

a second display circuit having a storage capacitor for storing an analog image signal from said corresponding one of drain lines in response to a scan signal from said corresponding one of gate lines, wherein the signal stored in said storage capacitor is supplied to said display element;

wherein said display pixel further comprises a display circuit selector for selectively supplying an image signal from said corresponding one of drain lines to said first or second display circuit;

and further including an output selector which selectively supplies data stored in one of said first display circuit and said second display circuit to said display element.

11. (Withdrawn): A display apparatus of claim 9 10, wherein  
said corresponding one of drain lines is constructed from a line for digital image signals and a line for analog image signals, and  
said first display circuit is connected to said line for digital image signals and said second display circuit is connected to said line for analog image signals.

12. (Previously Presented): A display apparatus, comprising:  
a plurality of gate lines provided in one direction of a substrate;  
a plurality of drain lines provided in a direction intersecting with said gate lines; and

a plurality of display pixels, each of which is selected by a scan signal supplied from corresponding one of said plurality of gate lines, and which is supplied with an image signal from corresponding one of said plurality of drain lines; wherein

each of said plurality of display pixels comprises:

a display element;

a first display circuit having a storing circuit, for storing a digital image signal from said corresponding one of drain lines in response to a scan signal from said corresponding one of gate lines, and a signal selector which is operated based on data stored at said storing circuit for selecting an output signal from among two or more display signals and supplying said selected signal to said display element; and

a second display circuit having a storage capacitor for storing an analog image signal from said corresponding one of drain lines in response to a scan signal from said corresponding one of gate lines, wherein the signal stored in said storage capacitor is supplied to said display element;

wherein said display pixel further comprises a data selector for selectively supplying an output signal from said first or second display circuit to said display element.

13. (Previously Presented): A display apparatus of claim 10, wherein said storing circuit comprises a predetermined number of storing elements, said number corresponding to the number of bits in said digital image signal; and

said signal selector selects a signal to be supplied to said display element from among a predetermined number of signals, said number corresponding to the number of bits in said digital image signal.

14. (Previously Presented): A display apparatus of claim 10, wherein, said storing circuit stores said digital image signal using one or more inverters.
15. (Previously Presented): A display apparatus of claim 10, wherein said storing circuit stores said digital image signal using one or more inverters and a capacitor.
16. (Previously Presented): A display apparatus of claim 10, wherein, said plurality of display pixels is capable of displaying a still image.
17. (Previously Presented): A display apparatus of claim 10, wherein, after a still image is written to each of said plurality of display pixels as a digital image signal, operations of driving circuits for driving said plurality of display pixels are stopped until a new digital image signal is written to the same display pixels.
18. (Previously Presented): A display apparatus of claim 10, wherein, said display apparatus is a liquid crystal display apparatus; and said display element includes a liquid crystal capacitor and a pair of electrodes for driving said liquid crystal capacitor.
19. (Original): A display apparatus of claim 18, wherein, said pair of electrodes for driving said liquid crystal capacitor comprises an individual display electrode for each display pixel and a counter electrode provided to face said display electrode; and

at least one of the signals selected by said signal selector is an alternating current voltage signal which oscillates around the voltage of said counter electrode.

20. (Currently Amended): A display apparatus, comprising:
- a plurality of gate lines provided in one direction of a substrate;
  - a plurality of drain lines provided in a direction intersecting with said gate lines; and
  - a plurality of display pixels, each of which is selected by a scan signal supplied from corresponding one of said plurality of gate lines, and which is supplied with an image signal from corresponding one of said plurality of drain lines; wherein
    - each of said plurality of display pixels comprises:
      - a display element;
      - a first display circuit having a storing circuit, for storing a digital image signal from said corresponding one of said plurality of drain lines in response to a scan signal from said corresponding one of said plurality of gate lines; and
      - a second display circuit having a storage capacitor for storing an analog image signal from said corresponding one of said plurality of drain lines in response to a scan signal from said corresponding one of said plurality of gate lines;
- and further including an output selector which selectively supplies data stored in one of said first display circuit and said second display circuit to said display element.

21. (Previously Presented): A display apparatus of claim 10, wherein

said display pixel further comprises a display circuit selector for selectively supplying an image signal from said corresponding one of drain lines to said first or second display circuit,

said display circuit selector is switched in response to a switching signal, and

said switching signal is a signal common to a plurality of pixels.

22. (Currently Amended): A display apparatus comprising a plurality of display pixels, wherein each of said display pixels comprises:

a pixel electrode;

a first storing circuit for storing digital data and outputting signals to said pixel electrode;

a second storing circuit for storing analog data and outputting signals to said pixel electrode; and

a storing circuit selector for switching between said first and second storing circuits;

and further including an output selector which selectively supplies data stored in one of said first display circuit and said second display circuit to said display element.

23. (Previously Presented): A display apparatus of claim 22, wherein

said first storing circuit comprises a predetermined number of storing elements, said number corresponding to the number of bits in said digital image signal; and

further including a signal selector for selecting a signal to be supplied to said display element from among a predetermined number of signals, said number corresponding to the number of bits in said digital image signal.

24. (Previously Presented): A display apparatus of claim 22, wherein, said first storing circuit stores said digital image signal using one or more inverters.

25. (Previously Presented): A display apparatus of claim 22 wherein, said plurality of display pixels is capable of displaying a still image.

26. (Previously Presented): A display apparatus of claim 22, wherein, after a still image is written to each of said plurality of display pixels as a digital image signal, operations of driving circuits for driving said plurality of display pixels are stopped until a new digital image signal is written to the same display pixels.

27. (Previously Presented): A display apparatus of claim 22, wherein, said display apparatus is a liquid crystal display apparatus; and said display element includes a liquid crystal capacitor and a pair of electrodes for driving said liquid crystal capacitor.

28. (Previously Presented): A display apparatus comprising a plurality of display pixels, wherein each of said display pixels comprises:

a pixel electrode;

a first storing circuit for storing digital data;

a signal selector for selecting a signal for display from among a plurality of signals based on an output of said first storing circuit and for outputting the selected display signal to said pixel electrode;

a second storing circuit for storing analog data and for directly outputting the analog data to said pixel electrode; and



a storing circuit selector for switching between said first and second storing circuits.

29. (Previously Presented): A display apparatus of claim 28, wherein said first storing circuit comprises a predetermined number of storing elements, said number corresponding to the number of bits in said digital image signal; and

said signal selector selects a signal to be supplied to said display element from among a predetermined number of signals, said number corresponding to the number of bits in said digital image signal.

30. (Previously Presented): A display apparatus of claim 28, wherein, said first storing circuit stores said digital image signal using one or more inverters.

31. (Previously Presented): A display apparatus of claim 28, wherein, said plurality of display pixels is capable of displaying a still image.

32. (Previously Presented): A display apparatus of claim 28, wherein, after a still image is written to each of said plurality of display pixels as a digital image signal, operations of driving circuits for driving said plurality of display pixels are stopped until a new digital image signal is written to the same display pixels.

33. (Previously Presented): A display apparatus of claim 28, wherein, said display apparatus is a liquid crystal display apparatus; and said display element includes a liquid crystal capacitor and a pair of electrodes for driving said liquid crystal capacitor.

34. (Previously Presented): A display apparatus comprising a plurality of display pixels, wherein each of said display pixels comprises:

- a pixel electrode;
- a first storing circuit for storing digital data;
- a second storing circuit for storing analog data; and
- a memory selector for switching a digital display mode in which said first storing circuit is used in all of said display pixels and an analog display mode in which said second storing circuit is used in all of said display pixels.

35. (Previously Presented): A display apparatus of claim 34, wherein said first storing circuit comprises a predetermined number of storing elements, said number corresponding to the number of bits in said digital image signal; and

further including a signal selector for selecting a signal to be supplied to said display element from among a predetermined number of signals, said number corresponding to the number of bits in said digital image signal.

36. (Previously Presented): A display apparatus of claim 34, wherein, said first storing circuit stores said digital image signal using one or more inverters.

37. (Previously Presented): A display apparatus of claim 34, wherein, said plurality of display pixels is capable of displaying a still image.

38. (Previously Presented): A display apparatus of claim 34, wherein, after a still image is written to each of said plurality of display pixels as a digital image signal, operations of driving circuits for driving said plurality of

display pixels are stopped until a new digital image signal is written to the same display pixels.

39. (Previously Presented): A display apparatus of claim 34, wherein, said display apparatus is a liquid crystal display apparatus; and said display element includes a liquid crystal capacitor and a pair of electrodes for driving said liquid crystal capacitor.

40. (Withdrawn): A display apparatus comprising:  
a plurality of gate lines provided in one direction of a substrate;  
a plurality of drain lines provided in a direction intersecting with said gate lines; and

a plurality of display pixels, each of which is selected by a scan signal supplied from corresponding one of said plurality of gate lines, and which is supplied with an image signal from corresponding one of said plurality of drain lines; wherein

each of said plurality of display pixels comprises:

a display element;

a switching element which is operated based on a scan signal from corresponding one of said plurality of gate lines for capturing a one-bit digital image signal from corresponding one of said drain lines;

a storing circuit for storing said one-bit digital image signal supplied via said switching element; and

a signal selector which is operated based on the digital signal stored at said storing circuit for selecting an output signal from among two or more display signals and for supplying said selected signal to said display element.

41. (Withdrawn): A display apparatus, comprising:  
a plurality of gate lines provided in one direction of a substrate;  
a plurality of drain lines provided in a direction intersecting with said gate lines; and  
a plurality of display pixels, each of which is selected by a scan signal supplied from corresponding one of said plurality of gate lines, and which is supplied with an image signal from corresponding one of said plurality of drain lines; wherein  
each of said plurality of display pixels comprises:  
a display element;  
a storing circuit for storing a digital image signal from said corresponding one of said plurality of drain lines in response to a scan signal from said corresponding one of said gate lines; and  
a signal selector which is operated based on data stored at said storing circuit for selecting an output signal from among two or more display signals and for supplying said selected signal to said display element; and  
wherein said storing circuit stores said digital image signal using one or more inverters and a capacitor.

42. (Withdrawn): A display apparatus comprising:  
a plurality of gate lines provided in one direction of a substrate;  
a plurality of drain lines provided in a direction intersecting with said gate lines; and  
a plurality of display pixels, each of which is selected by a scan signal supplied from corresponding one of said plurality of gate lines, and which is supplied with an image signal from corresponding one of said plurality of drain lines; wherein

each of said plurality of display pixels comprises:

a display element;

a storing circuit which is operated based on a scan signal from corresponding one of said plurality of gate lines for storing a digital image signal having a size of two or more bits supplied from corresponding one of said drain lines; and

a signal selector which is operated based on the digital signal stored at said storing circuit for selecting an output signal from among a plurality of display signals and for supplying said selected signal to said display element.

43. (Withdrawn): A display apparatus of claim 41, wherein,  
said storing circuit comprises a predetermined number of storing elements, said number corresponding to the number of bits in said digital image signal; and  
said signal selector selects a signal to be supplied to said display element from among a predetermined number of signals, said number corresponding to the number of bits in said digital image signal.

44. (Withdrawn): A display apparatus of claim 41, wherein,  
said storing circuit stores said digital image signal using one or more inverters.

45. (Withdrawn): A display apparatus of claim 41, wherein,  
said plurality of display pixels is capable of displaying a still image.

46. (Withdrawn): A display apparatus of claim 41, wherein,  
after a still image is written to each of said plurality of display pixels as a digital image signal, operations of driving circuits for driving said plurality of

display pixels are stopped until a new digital image signal is written to the same display pixels.

47. (Withdrawn): A display apparatus of claim 41, wherein,  
said display apparatus is a liquid crystal display apparatus; and  
said display element includes a liquid crystal capacitor and a pair of electrodes for driving said liquid crystal capacitor.

48. (Withdrawn): A display apparatus of claim 47, wherein,  
said pair of electrodes for driving said liquid crystal capacitor comprises an individual display electrode for each display pixel and a facing electrode provided to face said display electrode; and  
at least one of the signals selected by said signal selector is an alternating current voltage signal which oscillates around the voltage of said facing electrode.

49. (Withdrawn): A display apparatus of claim 12, wherein,  
said display pixel further comprises a display circuit selector for selectively supplying an image signal from said corresponding one of drain lines to said first or second display circuit.

50. (New): A display apparatus according to claim 10, wherein,  
said output selector selectively supplies an output from said first display circuit or an output from said second display circuit to said display element according to a control signal which is common with a control signal of said display circuit selector.

51. (New): A display apparatus according to claim 10, wherein,

said output selector is connected between said first display circuit and said second display circuit and said display element.

52. (New): A display apparatus according to claim 10, wherein, said analog image signal stored in said second display circuit is supplied to said display element through said output selector when said analog image signal is selected by said output selector.

53. (New): A display apparatus according to claim 20, wherein, said output selector is connected between said first display circuit and said second display circuit and said display element.

54. (New): A display apparatus according to claim 20, wherein, said analog image signal stored in said second display circuit is supplied to said display element through said output selector when said analog image signal is selected by said output selector.

55. (New): A display apparatus according to claim 22, wherein, said output selector is connected between said first display circuit and said second display circuit and said display element.

56. (New): A display apparatus according to claim 22, wherein, said analog image signal stored in said second display circuit is supplied to said display element through said output selector when said analog image signal is selected by said output selector.